

Housing - HC-EVO-B06-HHFS-EL-AL - 1411447

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



HEAVYCON EVO sleeve housing, EMC version, without powder coating, with bayonet flange for EVO screw connection, B6, for single locking latch, height: 80 mm, without EVO screw connection.

Why buy this product

Flexible cable outlet direction, lateral or straight



Key Commercial Data

Packing unit	1 STK
GTIN	4 046356 932455
GTIN	4046356932455

Technical data

Dimensions

Height	80 mm
Width	44 mm
Length	60 mm

Ambient conditions

Degree of protection of housing (IP)	IP66
	IP67
Degree of protection of housing (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Ambient temperature (operation)	-40 °C 125 °C

General

Note	For contact inserts HC-B6, BB10, DD24, M Tall housings for extra large wiring space
Size	B6
Housing type	Sleeve housing



Housing - HC-EVO-B06-HHFS-EL-AL - 1411447

Technical data

General


Color	gray aluminum		
Locking type	for single locking latch		
No. of cable outlets	1		
Cable outlet	straight		
	lateral		
Screw connection	none		
Housing material	Die-cast aluminum, salt water resistant		
Housing surface material	uncoated		
Connection	The sleeve base housing must be supplemented with the EVO screw connection. The EVO screw connection is available in 4 sizes. It enables the creation of a straight or a lateral cable outlet. The EVO screw connection is assembled by hand or using a pipe wrench.		


Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing





Dimensional drawing

Approvals

Approvals

Approvals

GL / UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approval details



Housing - HC-EVO-B06-HHFS-EL-AL - 1411447

Approvals

GL	GL	http://exchange.dnv.com/tari/	6196614 HH
UL Recognized	<i>9</i> 1	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E255026
cUL Recognized	. A L	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E255026
EAC	ERE		RU C- DE.Al30.B.01102
cULus Recognized	c 911 us	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	

Phoenix Contact 2018 @ - all rights reserved <code>http://www.phoenixcontact.com</code>

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com