

SPECIFICATIONS				
PARAMETERS	VALUES	UNITS		
RATED INPUT POWER	5	W		
MAX INPUT POWER	8	W		
IMPEDANCE	8 ± 15%	OHM		
OUTPUT SPL @ 1W/0.5M	86 ± 3	dBA		
(AT 0.6, 0.8, 1.0, 1.2 kHz)	00 ± 3	UBA		
DISTORTION (MAX.)	5%	-		
RESONANT FREQUENCY	240 ± 20%	Hz		
FREQUENCY RANGE	240 ~ 18,000	Hz		
HOUSING MATERIAL	METAL	-		
CONE MATERIAL	PAPER	-		
MAGNET MATERIAL	FERRITE	-		
OPERATING TEMPERATURE	-25 ~ +70	°C		
WEIGHT	128.44	grams		

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

©2003, Projects Unlimited Inc.

)		REVISION HISTORY			
	LTR	DESCRIPTION	DATE	APPROVED	
	-	RELEASED FROM ENGINEERING	8/16/2005		
	Α	REVISED MAGNET DIAMETER	12/19/2007	R.W.	
	В	REVISED HEIGHT & HOLE DIMENSIONS	1/29/2009	B.R.	
	С	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	1/29/2009	B.R.	
	D	REVISED OPERATING TEMPERATURE	2/9/2012	C.W.	







NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

UNLESS OTHERWISE SPECIFIED:	~
DIMENSIONS ARE IN MILLIMETERS.	SIZE
TOLERANCES ARE ±0.5 AND	A3
ANGLES ARE ±3°.	

AS09008PO-2-R.idw

J.A.F.	8/16/2005	В	,
	PUI audic a projects unlimited oc	Inc	
	1	, , ,	-

Date

Designed by

Checked by	Date	Approved by	Date	Drawn Date	
B.R.	8/16/2005	E.P.	8/16/2005	1/29/2009	
AS09008PO-2-R					

Speaker Edition Sheet 1/1