

# Introducing Raychem Side Entry Bushing (SEB)



# **Side Entry Bushing**



### **KEY FEATURES**

Fewer wraps needed than conventional silicone tapes

High temperature resistant silicone material rated to 180°C

Trim to fit capabilities. Fit any size saddle clamp/wire bundle combination

Thermally formed so it naturally conforms to circular wire bundles

Re-usable

6 standard sizes available

No adhesive layer for easy removal

### **DESCRIPTION**

Pre-coiled side entry reusable silicone bushing designed to be used in high temperature applications where tape or other molded grommets are used.

One strip of this Side Entry Bushing replaces as much as 6 feet and 40 wraps of traditional tapes. The material is crosslinked and thermoformed to naturally conform to the tight bundle configuration of its application.

The standard Side Entry Bushing has no adhesive layer, so it is easily removed and can be re-used often after repairs have been made.

### **APPLICATIONS**

Used in a non-environmentally sealed backshell (also known as a saddle clamp) and in clamping and wire management applications

### STANDARDS & SPECS

Conforms to Mil Standard AMS-DTL-23053/10, MIL-PRF-46846 Type II Class 1 and Tyco Electronics RT-1140

### ORDERING INFORMATION

25 per bag

### **MATERIALS**

Flexible, flame-retardant, silicone elastomer strip

### **ELECTRICAL**

Volume resistance: 10E11 OHM-CM min.

Dielectric strength: 350 V/mil. min.

Operating temperature range: -75°C to +180°C

### PHYSICAL OR OTHER PROPERTIES


Durometer Shore A: 60 +/- 5




## **PART NUMBERS**














Part Number	E Ref	D Ref	H ± 10%	L±10%	W±10%	Bundle O.D. Minimum	
SEB-A	.27	.30	.40	1.00	.06	.05	
	(6.9)	(7.6)	(10.2)	(25.4)	(1.5)	(1.3)	
SEB-B	.35	.40	.40	2.00	.06	.05	
	(8.9)	(10.2)	(10.2)	(50.8)	(1.5)	(1.3)	
SEB-C	.48	.53	.50	3.00	.06	.05	
	(12.2)	(13.5)	(12.7)	(76.2)	(1.5)	(1.3)	
SEB-D	.55	.60	.60	4.00	.06	.10	
	(14.0)	(15.2)	(15.2)	(101.6)	(1.5)	(2.5)	
SEB-E	.65	.70	.60	6.00	.06	.30	
	(16.5)	(17.8)	(15.2)	(152.4)	(1.5)	(7.6)	
SEB-F	.85	.88	.60	9.00	.06	.30	
	(21.6)	(22.4)	(15.2)	(228.6)	(1.5)	(7.6)	

Dimensions are in inches, metric in brackets.

Numbe of wraps will vary for each size.

### FOR MORE INFORMATION

### **Technical Support**

Internet: www.tycoelectronics.com/ADM
E-mail: product.info@tycoelectronics.com

 JSA:
 +1 (800) 522-6752

 Canada:
 +1 (905) 470-4425

 Mexico:
 +52 (0) 55-1106-0814

 C. America:
 +52 (0) 55-1106-0814

 South America:
 +55 (0) 11-2103-6000

 Germany:
 +49 (0) 6251-133-1999

 Great Britain:
 +44 (0) 8706-080208

 France:
 +33 (0) 1-3420-8686

 Netherlands:
 +31 (0) 73-6246-999

 China:
 +86 (0) 400-820-6015

**Tyco Electronics Corporation** 

Harrisburg, PA

ty coelectronics.com

Copyright 2011 Tyco Electronics Corporation

TE (Logo) and Tyco Electroncis are trademarks.

