



**NOTES:**

**1. Electrical Specifications:**

- Meets USB 2.0 specifications
- Low level Contact Resistance: 30 mOhm max.
- Insulation Resistance 1000 MOhm min.
- Current Rating: 1.5 A max. @ 25°C
- DWV: 500 VAC/60s at sea level
- Operating Temperature: -40°C to +80°C

**2. Material and Finish:**

- Coupling Ring: Polyester (Black); UL94 V-0
- Plug Housing: Polyester (Black); UL94 V-0
- Interfacial Seal: Silicon, Color: White
- Cable Gland: PA (Black); UL94 V-0
- Cable Gland Seal: NBR, Color: Black
- USB Insulator: PBT, UL 94V-0, Color: White
- USB Metal Shell: SPCC. Nickel plated
- USB Contact: Copper Alloy, 30 u" min. Au over 40 u" min. Nickel Plated

**3. Shielded USB Cable Configuration**

**AWM 2725 AWG28/1p + AWG24/2c, OD: 4.5 mm Color: black**

**4. RoHS compliant**

Directive 2002/95/EC RoHS Compliant

Cable Length L	Part Number
2 m	17-200811
3 m	17-200821
4.5 m	17-200831

THIS DRAWING MAY NOT BE COPIED, OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION <b>DO NOT ALTER CAD DRAWING BY HAND</b>	Customer:			Tolerance Unless otherwise specified 0 PLC ±0.30 1 PLC ±0.20 2 PLC ±0.10 3 PLC ±0.05 ANGLES ±1°		Scale: 1.5:1	Dim. in m	
	Name	Title	Approval Date			Material: See Notes		
				2009	Date	Name	Title: USB Patch Cord	
				Draw.	Jun. 20	Vincent Ke	USB 2.0 Type A Plug (Strain Relief)	
				Appd.	Jun. 20	J. chaudry	to USB 2.0 Type A (Strain Relief)	
				Norm			Drawing No.: 17K1A244	
				D-old			Part No.: SEE P/N ABOVE	
	a	original					DIN A3	
	Rev.	Changes	Date	Name				Sheet 1/1