

Housing - HC-STA-D07-BWSCM-PL-BK - 1419278

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Panel mounting base D7, with single locking latch, material: PA, protective cover material: PA, height: 25.5 mm, cable gland: none, support sleeve: no, protective cover: yes, Standard, for pin inserts



Key Commercial Data

Packing unit	1 STK
GTIN	4 055626 160283
GTIN	4055626160283

Technical data

Dimensions

Height	25.5 mm
Width	34.2 mm
Length	24.2 mm
Length of the assembly cutout	21 mm
Width of the assembly cutout	21 mm

Ambient conditions

Degree of protection of housing (IP)	IP66
Ambient temperature (operation)	-20 °C 100 °C

General

Note	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05, Q07, Q12	
Size	D7	
Housing type	Panel mounting base	
Color	black	
Locking type	with single locking latch	
Screw connection	none	
Protective cover	yes	



Housing - HC-STA-D07-BWSCM-PL-BK - 1419278

Technical data

General

Housing material	РА
Material lock	РА
Material, protective cover	РА
Flammability rating according to UL 94	V0 (Polyamide housing)

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50	
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"	

Drawings

Dimensional drawing



Dimensional drawing







Mounting cutout

Approvals

Approvals

Approvals

EAC / GL

Ex Approvals



Housing - HC-STA-D07-BWSCM-PL-BK - 1419278

Approvals

Approval details

EAC	EAC		RU C- DE.AI30.B.01102
GL	GL	http://exchange.dnv.com/tari/	6196614 HH

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com