



## N-Channel FREDFET

Power MOS 8™ is a high speed, high voltage N-channel switch-mode power MOSFET. This 'FREDFET' version has a drain-source (body) diode that has been optimized for high reliability in ZVS phase shifted bridge and other circuits through reduced  $t_{rr}$ , soft recovery, and high recovery dv/dt capability. Low gate charge, high gain, and a greatly reduced ratio of  $C_{rss}/C_{iss}$  result in excellent noise immunity and low switching loss. The intrinsic gate resistance and capacitance of the poly-silicon gate structure help control di/dt during switching, resulting in low EMI and reliable paralleling, even when switching at very high frequency.



APT42F50B      APT42F50S

Single die FREDFET



### FEATURES

- Fast switching with low EMI
- Low  $t_{rr}$  for high reliability
- Ultra low  $C_{rss}$  for improved noise immunity
- Low gate charge
- Avalanche energy rated
- RoHS compliant 

### TYPICAL APPLICATIONS

- ZVS phase shifted and other full bridge
- Half bridge
- PFC and other boost converter
- Buck converter
- Single and two switch forward
- Flyback

### Absolute Maximum Ratings

Symbol	Parameter	Ratings	Unit
$I_D$	Continuous Drain Current @ $T_C = 25^\circ\text{C}$	42	A
	Continuous Drain Current @ $T_C = 100^\circ\text{C}$	27	
$I_{DM}$	Pulsed Drain Current <sup>①</sup>	135	
$V_{GS}$	Gate-Source Voltage	$\pm 30$	V
$E_{AS}$	Single Pulse Avalanche Energy <sup>②</sup>	930	mJ
$I_{AR}$	Avalanche Current, Repetitive or Non-Repetitive	21	A

### Thermal and Mechanical Characteristics

Symbol	Characteristic	Min	Typ	Max	Unit
$P_D$	Total Power Dissipation @ $T_C = 25^\circ\text{C}$			625	W
$R_{\theta JC}$	Junction to Case Thermal Resistance			0.20	°C/W
$R_{\theta CS}$	Case to Sink Thermal Resistance, Flat, Greased Surface		0.11		
$T_J, T_{STG}$	Operating and Storage Junction Temperature Range	-55		150	°C
$T_L$	Soldering Temperature for 10 Seconds (1.6mm from case)			300	
$W_T$	Package Weight		0.22		oz
			6.2		g
Torque	Mounting Torque (TO-247 Package), 6-32 or M3 screw			10	in-lbf
				1.1	N·m

## Static Characteristics

$T_J = 25^\circ\text{C}$  unless otherwise specified

AP42F50B\_S

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
$V_{BR(DSS)}$	Drain-Source Breakdown Voltage	$V_{GS} = 0\text{V}$ , $I_D = 250\mu\text{A}$	500			V
$\Delta V_{BR(DSS)}/\Delta T_J$	Breakdown Voltage Temperature Coefficient	Reference to $25^\circ\text{C}$ , $I_D = 250\mu\text{A}$		0.60		$\text{V}/^\circ\text{C}$
$R_{DS(on)}$	Drain-Source On Resistance <sup>③</sup>	$V_{GS} = 10\text{V}$ , $I_D = 21\text{A}$		0.11	0.13	$\Omega$
$V_{GS(th)}$	Gate-Source Threshold Voltage	$V_{GS} = V_{DS}$ , $I_D = 1\text{mA}$	2.5	4	5	V
$\Delta V_{GS(th)}/\Delta T_J$	Threshold Voltage Temperature Coefficient			-10		$\text{mV}/^\circ\text{C}$
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS} = 500\text{V}$			250	$\mu\text{A}$
		$V_{GS} = 0\text{V}$			1000	
$I_{GSS}$	Gate-Source Leakage Current	$V_{GS} = \pm 30\text{V}$			$\pm 100$	nA

## Dynamic Characteristics

$T_J = 25^\circ\text{C}$  unless otherwise specified

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
$g_{fs}$	Forward Transconductance	$V_{DS} = 50\text{V}$ , $I_D = 21\text{A}$		32		S
$C_{iss}$	Input Capacitance	$V_{GS} = 0\text{V}$ , $V_{DS} = 25\text{V}$ $f = 1\text{MHz}$		6810		$\text{pF}$
$C_{rss}$	Reverse Transfer Capacitance			90		
$C_{oss}$	Output Capacitance			735		
$C_{o(cr)}^{\text{④}}$	Effective Output Capacitance, Charge Related	$V_{GS} = 0\text{V}$ , $V_{DS} = 0\text{V}$ to $333\text{V}$		425		$\text{pF}$
$C_{o(er)}^{\text{⑤}}$	Effective Output Capacitance, Energy Related			215		
$Q_g$	Total Gate Charge	$V_{GS} = 0$ to $10\text{V}$ , $I_D = 21\text{A}$ , $V_{DS} = 250\text{V}$		170		$\text{nC}$
$Q_{gs}$	Gate-Source Charge			38		
$Q_{gd}$	Gate-Drain Charge			80		
$t_{d(on)}$	Turn-On Delay Time	<b>Resistive Switching</b> $V_{DD} = 333\text{V}$ , $I_D = 21\text{A}$ $R_G = 4.7\Omega^{\text{⑥}}$ , $V_{GG} = 15\text{V}$		29		$\text{ns}$
$t_r$	Current Rise Time			35		
$t_{d(off)}$	Turn-Off Delay Time			80		
$t_f$	Current Fall Time			26		

## Source-Drain Diode Characteristics

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit	
$I_s$	Continuous Source Current (Body Diode)	MOSFET symbol showing the integral reverse p-n junction diode (body diode)			42	A	
$I_{SM}$	Pulsed Source Current (Body Diode) <sup>①</sup>				135		
$V_{SD}$	Diode Forward Voltage	$I_{SD} = 21\text{A}$ , $T_J = 25^\circ\text{C}$ , $V_{GS} = 0\text{V}$			1.2	V	
$t_{rr}$	Reverse Recovery Time	$I_{SD} = 21\text{A}^{\text{③}}$ $di_{SD}/dt = 100\text{A}/\mu\text{s}$ $V_{DD} = 100\text{V}$	$T_J = 25^\circ\text{C}$		225	ns	
			$T_J = 125^\circ\text{C}$		400		
	Reverse Recovery Charge		$T_J = 25^\circ\text{C}$		1.00	$\mu\text{C}$	
			$T_J = 125^\circ\text{C}$		2.50		
	Reverse Recovery Current		$T_J = 25^\circ\text{C}$		9.1	A	
			$T_J = 125^\circ\text{C}$		12.9		
$dv/dt$	Peak Recovery $dv/dt$	$I_{SD} \leq 21\text{A}$ , $di/dt \leq 1000\text{A}/\mu\text{s}$ , $V_{DD} = 333\text{V}$ , $T_J = 125^\circ\text{C}$			20	V/ns	

① Repetitive Rating: Pulse width and case temperature limited by maximum junction temperature.

② Starting at  $T_J = 25^\circ\text{C}$ ,  $L = 4.22\text{mH}$ ,  $R_G = 25\Omega$ ,  $I_{AS} = 21\text{A}$ .

③ Pulse test: Pulse Width < 380 $\mu\text{s}$ , duty cycle < 2%.

④  $C_{o(cr)}$  is defined as a fixed capacitance with the same stored charge as  $C_{oss}$  with  $V_{DS} = 67\%$  of  $V_{(BR)DSS}$ .

⑤  $C_{o(er)}$  is defined as a fixed capacitance with the same stored energy as  $C_{oss}$  with  $V_{DS} = 67\%$  of  $V_{(BR)DSS}$ . To calculate  $C_{o(er)}$  for any value of  $V_{DS}$  less than  $V_{(BR)DSS}$ , use this equation:  $C_{o(er)} = -1.84E-7/V_{DS}^2 + 3.75E-8/V_{DS} + 1.05E-10$ .

⑥  $R_G$  is external gate resistance, not including internal gate resistance or gate driver impedance. (MIC4452)

Microsemi reserves the right to change, without notice, the specifications and information contained herein.




Figure 1, Output Characteristics



Figure 3,  $R_{DS(ON)}$  vs Junction Temperature

Figure 5, Gain vs Drain Current




Figure 7, Gate Charge vs Gate-to-Source Voltage




Figure 2, Output Characteristics




Figure 4, Transfer Characteristics




Figure 6, Capacitance vs Drain-to-Source Voltage







Figure 8, Drain Current vs Source-to-Drain Voltage



**Figure 9, Forward Safe Operating Area**




**Figure 10, Maximum Forward Safe Operating Area**



**Figure 12. Maximum Effective Transient Thermal Impedance Junction-to-Case vs Pulse Duration**

## **TO-247 (B) Package Outline**


e1 SAC: Tin, Silver, Copper



**Dimensions in Millimeters (Inches)**

# D<sup>3</sup>PAK Package Outline

(e3) 100% Sn Plated



**Dimensions in Millimeters (Inches)**