

SPECIFICATIONS

Typical Values Polypropylene Permanently 10E2 - 10E4 ohms Yes Yes -17° F to +230° F 324° F

Features

- Provides physical protection, with conductive material providing reliable path-to-ground
- Efficient means of transporting items to the assembly area, and empty totes back to the store room for refilling
- Extremely durable; includes steel reinforcing frame and rolled over side construction (double thickness)
- · Ships assembled
- Conductive 10E2 10E4 ohm material provides reliable path-toground
- Superior strength and durability; made from extruded, high impact polypropylene materials
- Chemical and moisture resistant
- Ideal for use where corrugated and/or paper products cannot be used
- · Economical alternative to injection molded products
- Reusable, ensuring best value*
- Made in America

Item No.	Size O.D L x W x D
39140	18 x 12 x 6
39141	27-1/4 x 12 x 6
39142	27-1/4 x 18 x 6

RoHS Compliance Statement None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Protektive Pak Inc. letter on-line at <u>ProtektivePak.com</u>.



DATE:

8/07

Plastek[™] Nesting Totes

PROTEKTIVE PAK

PROTEKTIVE PAK 13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578, FAX (909) 363-7331 www.protektivepak.com

DRAWING NUMBER 39140