
SPECIFICATIONS			
PARAMETERS	VALUES	UNITS	
RATED INPUT POWER	1	W	
MAX INPUT POWER	2	W	
IMPEDANCE	8 ± 15%	ОНМ	
OUTPUT SPL @ 1W/0.5M	84 ± 3	dDA	
(AT 1.0, 1.2, 1.5, 2.0 kHz)	04 ± 3	dBA	
DISTORTION (MAX.)	5%	-	
RESONANT FREQUENCY	450 ± 20%	Hz	
FREQUENCY RANGE	450 ~ 20000	Hz	
HOUSING MATERIAL	ABS	-	
CONE MATERIAL	PAPER	-	
MAGNET MATERIAL	Nd-Fe-B	-	
OPERATING TEMPERATURE	-20 ~ +60	°C	
WEIGHT	13	grams	

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.


©2003, Projects Unlimited Inc.

REVISION HISTORY				
LTR	DESCRIPTION	DATE	APPROVED	
-	RELEASED FROM ENGINEERING	6/29/2006		
Α	REVISED CONE MATERIAL	3/16/2007	R.W.	
В	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	5/19/2008	B.R.	



 $-28.3 \pm 0.2$  $-22.5 \pm 0.1$  $40 \pm 0.2$  $34 \pm 0.1$ 

Designed by



## NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

UNLESS OTHERWISE SPECIFIED:	OLZE
DIMENSIONS ARE IN MILLIMETERS,	SIZE
TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.	<b>A</b> 3
AS04008PO-2-R.idw	

J.D.	6/28/2006	E	E.P.	6
	pul.			
	a projects unlimited co			

Checked by	/ Date	Approved by	Date	Drawn Date
E.P.	6/28/2006	B.R.	6/28/2006	5/19/2008
AS04008PO-2-R				

Sheet

1/1

Edition Speaker