
SPECIFICATIONS					
PARAMETERS	VALUES	UNIT			
DIRECTIVITY	OMINI	-			
SENSITIVTY	-44 ± 3	dB			
STANDARD OPERATING VOLTAGE	2	Vdc			
MAX OPERATING VOLTAGE	10	Vdc			
CURRENT CONSUMPTION (MAX)	0.5	mA			
IMPEDANCE	2.2	KOhm			
SIGNAL TO NOISE RATIO (MIN.)	60	dB			
TERMINAL	PIN	-			
INTERNAL CAPACITOR	N/A	pF			

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

©2003, Projects Unlimited Inc.

B →

REVISION HISTORY								
LTR	DESCRIPTION	DATE	APPROVED					
-	RELEASED FROM ENGINEERING	9/8/2006						
Α	REVISED IP RATING	7/2/2008	B.R.					
В	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	10/25/2010	B.R.					



- **NOTES:** 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.

**MICROPHONE** 

 $-2.8 \pm 0.3$ 

- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.
- 4. PART IS IP57 RATED.

 $\emptyset 6 \pm 0.1$ 

5. ASSEMBLY IS WASHABLE WITH BOOT IN PLACE.



**ASSEMBLY** 

igned by	Date	Checked by		Date	Approved by	Date		Drawn Date
J.D.	9/8/2006	B.R.		9/8/2006	R.W.	9/8/20	06 10	0/25/2010
pul.			POW-2744P-B-R					
audio nc a projects unlimited company		Microphone				Edition -	Sheet 1 / 1	

A-A (9:1)