

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

# USB 3.1 Gen 1 USB-C to VGA Adapter with USB-A, USB-C PD Charging & Gigabit Ethernet, Thunderbolt 3 Compatible, 1080p, White

MODEL NUMBER: U444-06N-VGU-C











Mini docking station adds VGA, USB-A, USB-C PD charging and Gigabit Ethernet ports to the USB-C or Thunderbolt 3 port on your tablet, laptop, notebook, MacBook, Chromebook, smartphone or PC.

#### Description

The U444-06N-VGU-C USB 3.1 Gen 1 USB-C to VGA Adapter expands the potential of your tablet, laptop, Chromebook, MacBook, smartphone or PC's USB-C or Thunderbolt 3 port. It's ideal for transmitting 1080p video to a large display, adding a thumb drive or other USB peripheral, powering and charging a PD Charging-compliant mobile device, and connecting to a Gigabit Ethernet network—all at the same time.

With a source device that also supports USB DisplayPort Alternate Mode, you can extend video from your primary display to another, duplicate the same video on both displays, or change the second display to your primary.

The plug-and-play U444-06N-VGU-C requires no software, drivers or external power. Connect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

To send HD video to a VGA television, projector or monitor, connect the VGA port to the display using a VGA cable (sold separately). The VGA port supports HD video resolutions up to 1920 x 1080 (1080p) at 60 Hz.

The USB-A port accepts USB peripherals, such as a flash drive, mouse, keyboard or printer. It supports fast USB 3.1 Gen 1 data transfer rates up to 5 Gbps and is backward compatible with previous USB generations. The dedicated BC 1.2-compliant port provides up to 1.5A of fast-charging power to mobile devices.

The USB-C Power Delivery (PD) port provides power and charging to the PD Charging-compliant device (such as a MacBook or Chromebook) the U444-06N-VGU-C is connected to. Connect the device's AC wall charger to the USB-C PD port, which supports power input up to 20V 3A (60W).

The RJ45 port offers access to a Gigabit Ethernet network when no Wi-Fi is available or when a wired connection offers faster speeds. Connect using a UTP cable (sold separately), and enjoy true

# **Highlights**

- Supports USB DisplayPort
   Alternate Mode for transmitting
   video
- Supports HD video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- Supports true 10/100/1000
   Mbps Ethernet network speeds
- USB-C PD charging port supports power input up to 20V 3A (60W)
- BC 1.2-compliant USB-A port provides up to 1.5A of fastcharging power
- Plug-and-play operation with no software or drivers required

### **System Requirements**

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate
   Mode
- Display device with VGA input (VGA port)

# **Package Includes**

- U444-06N-VGU-C USB 3.1 Gen
   1 USB-C to VGA Adapter, White
- Owner's manual



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

10/100/1000 Mbps Ethernet speeds for fast data transfers.

#### **Features**

#### Mini Docking Station Turns Your Device's USB-C Port into a Multiport Workstation

- Ideal for transmitting video to a large display, adding a USB peripheral, powering and charging a PD
   Charging-compliant mobile device, and connecting to a Gigabit Ethernet network simultaneously
- Plug-and-play operation with no software, drivers or external power required
- · About the size of a credit card for easy carrying in a pocket, purse or laptop bag

#### Transmit Crystal-Clear 1080p Video to VGA Display

- Compatible with USB-C or Thunderbolt 3 source devices that support USB DisplayPort Alternate Mode
- Supports HD video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- Extends video from your primary display to another
- Duplicates the same video on 2 displays
- Converts a secondary display to your primary display

# Connect a USB Peripheral

- USB-A port accepts flash drives, mice, keyboards, printers and other USB peripherals
- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- Backward compatible with USB 2.0 and USB 1.1
- BC 1.2-compliant port provides up to 1.5A of fast-charging power to mobile devices.

#### **Charge a Connected Device**

- USB-C PD port connects to wall charger to power and charge the connected PD Charging-compliant USB-C/Thunderbolt 3 device
- Supports power input up to 20V 3A (60W)

## **Access a Wired Gigabit Ethernet Network**

- RJ45 port supports true 10/100/1000 Mbps network speeds
- Recommended for a faster wired network connection or getting online when no Wi-Fi is available

# **Built-In Cable with Reversible USB-C Connector**

• Fumble-free reversible USB-C plug connects in either direction for quick connection every time

# **Specifications**

OVERVIEW	
UPC Code	037332193728
Technology	Cat5/5e; Cat6; USB 3.1 (Gen 1); USB (all versions); VGA/SVGA
INPUT	
Bus Powered	Yes



Product Length (in.)	6.00	
PHYSICAL		
Shipping Dimensions (hwd / in.)	0.910 x 5.510 x 3.940	
Shipping Dimensions (hwd / cm)	2.31 x 14.00 x 10.01	
Shipping Weight (lbs.)	0.1300	
Shipping Weight (kg)	0.06	
Unit Packaging Type	Box	
Unit Dimensions (hwd / in.)	0.65 x 3.8 x 1.6	
Unit Weight (lbs.)	0.11	
Unit Weight (kg)	0.05	
Material of Construction	PVC and ABS	
Color	White	
Cable Jacket Rating	VW-1	
ENVIRONMENTAL		
Operating Temperature Range	32 to 113 F (0 to 45 C)	
Storage Temperature Range	14 to 158 F (-10 to 70 C)	
BTUs	7.6 BTU/Hr	
Power Consumption (Watts)	2.2	
Operating Humidity Range	10% to 85% RH, Non-Condensing	
Storage Humidity Range	5% to 90% RH, Non-Condensing	
Power Provided to Connected Device(s)	5V 0.9A (4.5W) Output (USB-A), Up to 20V 3A (60W) Input (USB-C)	
COMMUNICATIONS		
Network Speed	1Gbps	
IEEE Standards Supported	802.3; 802.3u; 802.3az; 802.3x	
CONNECTIONS		
Ports	4	
Side R. Connector 1	USB C (MALE)	
Side B - Connector 1	HD15 (FEMALE)	
Side B - Connector 2	USB 3.0 A (FEMALE)	
Side B - Connector 3	RJ45 (FEMALE)	
Side B - Connector 4	USB C (FEMALE)	
Connector Plating	Nickel	





FEATURES & SPECIFICATIONS		
Max Supported Video Resolution	1920 x 1080 (1080p) @60Hz	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
Driver Required	No	
Recommended Category Cable	Cat5/Cat5e/Cat6 Cables	
USB Power Delivery (PD) Charging Support	Yes	
Auto MDIX Support	Yes	
Full Duplex Support	Yes	
Suspend Mode Support	Yes	
Remote Wakeup Support	Yes	
CERTIFICATIONS		
Certifications	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>